

Laravel Project Setup Guide

1. Comad to create a **LARAVEL** project-
`composer create-project laravel/laravel project-name`
2. Inside **resources->views** paste all the HTML files
3. Rename them with the extension `.blade.php`
4. **To rename all the files at a click, open the terminal and paste the following command**
`Get-ChildItem .\resources\views -Recurse -File -Filter *.html |
Rename-Item -NewName { $_.BaseName + '.blade.php' }`
5. **To change all the CSS, JS, and image paths, use the following command**
`Get-ChildItem .\resources\views -Recurse -File -Include
.blade.php,.php,*.html | ForEach-Object {
$content = Get-Content $_.FullName -Raw
$content = $content -replace 'href="images/([^\"]+)"', 'href="{{
asset("assets/images/$1") }}"'
$content = $content -replace 'src="images/([^\"]+)"', 'src="{{
asset("assets/images/$1") }}"'
$content = $content -replace 'href="css/([^\"]+)"', 'href="{{
asset("assets/css/$1") }}"'
$content = $content -replace 'src="css/([^\"]+)"', 'src="{{
asset("assets/css/$1") }}"'
$content = $content -replace 'href="js/([^\"]+)"', 'href="{{
asset("assets/js/$1") }}"'
$content = $content -replace 'src="js/([^\"]+)"', 'src="{{ asset("assets/js/$1")
}}"'
$content = $content -replace 'href="rs-plugin/([^\"]+)"', 'href="{{
asset("assets/rs-plugin/$1") }}"'
$content = $content -replace 'src="rs-plugin/([^\"]+)"', 'src="{{
asset("assets/rs-plugin/$1") }}"'
Set-Content $_.FullName $content
}`
6. **In .ENV paste this-**

```
APP_NAME=Laravel  
APP_ENV=local  
APP_KEY=base64:Y/CmX+/aYAaSTLaIPwMwwTaO4wSxbM7QVRaDxoq6ir  
4=  
APP_DEBUG=true  
APP_URL=http://127.0.0.1:8000
```

APP_LOCALE=en
APP_FALLBACK_LOCALE=en
APP_FAKER_LOCALE=en_US

APP_MAINTENANCE_DRIVER=file

BCRYPT_ROUNDS=12

LOG_CHANNEL=stack
LOG_STACK=single
LOG_DEPRECATIONS_CHANNEL=null
LOG_LEVEL=debug

DB_CONNECTION=sqllite

SESSION_DRIVER=file
SESSION_LIFETIME=120
SESSION_ENCRYPT=false
SESSION_PATH=/
SESSION_DOMAIN=null

BROADCAST_CONNECTION=log
FILESYSTEM_DISK=local
QUEUE_CONNECTION=sync

CACHE_STORE=file

MEMCACHED_HOST=127.0.0.1

REDIS_CLIENT=phpredis
REDIS_HOST=127.0.0.1
REDIS_PASSWORD=null
REDIS_PORT=6379

MAIL_MAILER=log
MAIL_SCHEME=null
MAIL_HOST=127.0.0.1
MAIL_PORT=2525
MAIL_USERNAME=null
MAIL_PASSWORD=null
MAIL_FROM_ADDRESS="hello@example.com"
MAIL_FROM_NAME="\${APP_NAME}"

AWS_ACCESS_KEY_ID=
AWS_SECRET_ACCESS_KEY=

```
AWS_DEFAULT_REGION=us-east-1
AWS_BUCKET=
AWS_USE_PATH_STYLE_ENDPOINT=false
```

```
VITE_APP_NAME="${APP_NAME}"
```

7. Later, you can paste the following in the .env when you connect to the database

```
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=Your_database_name
DB_USERNAME=root
DB_PASSWORD=
SESSION_DRIVER=database
CACHE_STORE=database
QUEUE_CONNECTION=database
```